
Qseven - Evaluation Carrier 2.1







- ► Evaluation Carrier Board for Qseven 2.1 based Computer-on-Modules
- ▶ Broad range of interface options for design development flexibility
- Compliant with Qseven 2.1 specifications by SGET



The Oseven Evaluation Carrier 2.1 is designed to allow embedded application developers to get up and running quickly on the Oseven modular platform, giving them a head start on total system Simply select the Oseven module best suited for your application needs, install the module and you are to get started. The Qseven Evaluation Carrier is compliant with the Qseven 2.1 specifications and supports a of interface range options dedicated for low power applications including 1x Gigabit Ethernet support, SD-card socket, USB2.0 and mSATA, PCIe and many more.

The implementation of LVDS, HDMI DP++ and allows multimedia applications. The intelligent audio implementation allows also HDA and I2S to be used on the same audio connectors with Modules support the function. The rich feature set of the carrier increases the flexibility of highly sophisticated applications.

TECHNICAL INFORMATION

SPECIAL FEATURE	1x CAN Bus Interface, switchable audio interface, switchable display interface
I/O FEATURES	1x RS232, 2x miniPCIe with SIM card support, 2x PCIe, 1x CAN, 8x GPIO / 1x LPC
STORAGE	SD Card, mSATA, SATA
ETHERNET	1x GB LAN
DISPLAY	Dual channel 24 bit LVDS muxed with eDP and DP, HDMI Interface muxed with DP++ Interface
USB	1x USB 2.0 dual role, 2x USB3.0, 2x USB connected to mPCIe
POWER SUPPLY	ATX Power Supply Support, 12V Single supply, optional 3.0 -5.25V for module only (for module that support the feature)
PHYSICAL DIMENSIONS	200 x 210 mm
COMPLIANCE	Qseven 2.1 specifications by SGET
TEMPERATURE	Industrial temperature: -40 °C to +85 °C operating, -40 °C to +85 °C non-operating
HUMIDITY	93 % relative Humidity at 40 °C, non-condensing (according to IEC 60068-2-78)



ORDERING INFORMATION

ARTICLE

Qseven-Eval Carrier 2.1

PART NO.

81100-0000-00-0

DESCRIPTION

Qseven Evaluation Carrier for Qseven modules according to the Qseven 2.1 standard (without Qseven module)



ORDERING INFORMATION EUROPE, MIDDLE EAST

Lise-Meitner-Str. 3-5 86156 Augsburg

Germany

Tel.: + 49 821 4086 0 Fax: + 49 821 4086

111

info@kontron.com

NORTH AMERICA

9477 Waples Street San Diego, CA 92121

Tel.: + 1888 294 4558 Fax: + 1858 677 0898

info@us.kontron.com

ASIA PACIFIC & AFRICA

Plot 554 Lorong Perusahaan, Prai Free Trade Zone, Penang 13600, Malaysia

Tel.: +604 377 7178 Fax: +604 380 8182

Copyright © 2016 Kontron AG. All rights reserved. All data is for information purposes only and not guaranteed for legal purposes. Information has been carefully checked and is believed to be accurate, showers and the Kontron in the Kontron in the recember of the recember of the property of their respective cowners and are recognized. Specifications are subject to change without notice. \$MARC-5AAL-2016115. VIMH.